



Gütermann E

The experts choice for covering fabric edges

In counts 40 | 80 | 160 | 240



These texturised polyester threads are excellent for covering fabric edges and have a high degree of softness. They are suitable for a wide range of applications that include automatic overseaming. They can be used in lightweight and knitted fabrics as well as in bras, corsets and home furnishings.

www.guetermann.com

Gütermann

Gütermann E

E 121 - No. 240 | E 151 - No. 160 | E 382 - No. 80 | E 764 - No. 40

100 % Polyester - Texturised Sewing Threads

	E 121 – No. 240	E 151 – No. 160	E 382 – No. 80	E 764 – No. 40
Applications	For soft finishing of cut edges on light and medium-weight fabrics and knits.	For soft finishing of cut edges on light and medium-weight fabrics and knits.	For soft finishing of cut edges with good coverage, as looper and cover thread for swimwear and foundation garments.	For finishing raw edges on table cloths and curtains, decorative novelty seams.
Advantages	Suitable as a needle thread, therefore having a wide range of uses. Also very good for use with edging machines.			
	Very soft edge covering.	Very soft edge covering.	Very soft seams with good coverage.	Very high coverage and softness.
Make-up				
Size	Kingspools with 10.000 m and 30.000 m	Kingspools with 10.000 m and 24.000 m	Kingspools with 6.000 m and 12.000 m	Kingspools with 6.000 m
Shade range	Shade card Gütermann E			
Needle size	NM 70 – 90 / 10 – 14	NM 80 – 100 / 12 – 16	NM 90 – 110 / 14 – 18	NM 120 – 140 / 19 – 22
Technology				
Count	No./Tkt. 240 – dtex 120(1) – tex 12	No./Tkt. 160 – dtex 190(1) – tex 19	No./Tkt. 80 – dtex 380(2) – tex 38	No./Tkt. 40 – dtex 760(4) – tex 76
Average breaking strength	500 cN	750 cN	1.300 cN	2.300 cN
Average breaking extension	27 %	25 %	25 %	25 %
Boiling shrinkage	below 2 %			
Thermal shrinkage	below 3 %			
Fastness				
Fastness to water in accordance with DIN 54006	4 and better			
Fastness to perspiration in accordance with DIN 54020	4 and better			
Fastness to rubbing in accordance with DIN 54021	4 and better			
Fastness to organic solvents in accordance with DIN 54023	4 and better			
	www.guetermann.com 			